



NOTES:

1.MATERIAL:

- 1.1 Insulator:PBT+30%Glass Fiber (UL94V-0)
- 1.2 Contact: Brass
- 1.3 Contact Plated: Gold/Tin plated
- 1.4 Shell: Spcc, Nickle Plated

2.SPECIFICATION:

- 2.1 Current Rate: 5 Amps
- 2.2 Insulator Resistance: 1000M $\Omega$  Min. at 500V DC
- 2.3 Dielectric Strength: 500V AC Per minute
- 2.4 Operation Temperature: -55°C to+105°C
- 2.5 MAX PROCESSING TEMPERATURE :  
60 SECONDS IN 230°C AND 10 SECONDS IN 260°C

3.ALL MATERIALS/PROCESSES ARE ROHS COMPLIANT

UNIT	mm	Projection		Secon International Enterprise Co., Ltd.			
TOLERANCES				TITLE			
General Tolerance		Angle Tolerance		D-SUB connector 15 pin Female type			
x. = $\pm 0.5$		x. = $\pm 2^\circ$					
.x = $\pm 0.3$		.x = $\pm$					
.xx = $\pm$				PART NO. DSUB-SF15-TGB018			
DRAWN	Kevin	DATE	2007/2/27				
SCALE	1:1	SIZE	A4	SHEET	1/1	REV	A0