



MATERIALS:
 INSULATOR: P. B. T. 30% GLASS FIBER, UL94V-0
 CONTACT MATERIAL: BRASS OR PHOSPHOR BRONZE,
 GOLD FLASH OVER NICKEL

ELECTRICAL:
 CURRENT RATING: 1AMP.
 INSULATION RESISTANCE: 1000M Ω MIN.
 DIELECTRIC WITHSTANDING: 500VAC
 OPERATING TEMPERATURE: -40°C ~ +105°C

DIMENSION					
	A	B	A	B	
06P	12.18	05.08	24P	35.04	27.94
08P	14.72	07.62	26P	37.58	30.48
10P	17.26	10.16	30P	42.66	35.56
12P	19.80	12.70	34P	47.74	40.64
14P	22.34	15.24	36P	50.43	43.18
16P	24.88	17.78	40P	55.36	48.26
18P	27.42	20.32	44P	60.64	53.34
20P	29.96	22.86	50P	68.06	60.96

IDC-S CXX X - 2XX

IDC Socket Series
 Secount
 Socket Number of Contacts
 Package
 N: Nickel Plated
 G: Gold Plated
 Dual Row
 2: 2 parts
 3: 3 parts

UNIT	mm	S Secount International Enterprise Co., Ltd	
TOLERANCES		TITLE	
.x = ±0.25		2.54mm(0.1") pitch IDC Socket	
.xx = ±0.20		PART NO.	IDC-SCXX-2XX
DRAWN	DATE	SHEET	1/1
SCALE	SIZE	A4	REV